

# Q.POWER L-G5 315-335

## POLYCRYSTALLINE SOLAR MODULE

The new **Q.POWER L-G5** is the result of the continued evolution of our polycrystalline solar modules. Thanks to improved power yield, excellent reliability and high-level operational safety, the new **Q.POWER L-G5** generates electricity at a low cost (LCOE) and is suitable for a wide range of applications.



### SUPERIOR YIELD

High power output thanks to advanced 6-busbar technology and outstanding performance under real-life conditions.



### LOW LEVELISED COST OF ELECTRICITY

Higher yield per surface area, lower BOS costs, higher power classes and an efficiency rate of up to 17.5%.



### INNOVATIVE ALL-WEATHER TECHNOLOGY

Optimal yields, whatever the weather with excellent low-light and temperature behaviour.



### EXTREME WEATHER RATING

High-tech aluminium alloy frame, certified for high snow (5400 Pa) and wind loads (2400 Pa).



### MAXIMUM COST REDUCTIONS

Lower logistics costs due to higher module capacity per box.



### A RELIABLE INVESTMENT

Inclusive 12-year product warranty and 25-year linear performance warranty<sup>1</sup>.



<sup>1</sup> See data sheet on rear for further information.

### THE IDEAL SOLUTION FOR:




Ground-mounted  
solar power plants

Engineered in **Germany**

**Q CELLS**

## MECHANICAL SPECIFICATION

<b>Format</b>	1960mm × 991mm × 35mm (including frame)
<b>Weight</b>	22.5kg ± 5%
<b>Front Cover</b>	3.2mm thermally pre-stressed glass with anti-reflection technology
<b>Back Cover</b>	Multi-layer composite sheet
<b>Frame</b>	Anodised aluminium
<b>Cell</b>	6 × 12 polycrystalline solar cells
<b>Junction box</b>	Protection class IP67 or IP68, with bypass diodes
<b>Cable</b>	4mm <sup>2</sup> Solar cable; (+) ≥ 1200mm, (-) ≥ 1200mm
<b>Connector</b>	Intermateable connector with H4, MC4




## ELECTRICAL CHARACTERISTICS

POWER CLASS			315	320	325	330	335
<b>MINIMUM PERFORMANCE AT STANDARD TEST CONDITIONS, STC<sup>1</sup> (POWER TOLERANCE +5W / -0W)</b>							
Minimum	<b>Power at MPP<sup>2</sup></b>	<b>P<sub>MPP</sub></b> [W]	315	320	325	330	335
	<b>Short Circuit Current*</b>	<b>I<sub>SC</sub></b> [A]	9.11	9.15	9.20	9.30	9.40
	<b>Open Circuit Voltage*</b>	<b>V<sub>OC</sub></b> [V]	45.7	45.8	46.0	46.1	46.3
	<b>Current at MPP*</b>	<b>I<sub>MPP</sub></b> [A]	8.50	8.61	8.67	8.76	8.87
	<b>Voltage at MPP*</b>	<b>V<sub>MPP</sub></b> [V]	37.1	37.2	37.5	37.7	37.8
	<b>Efficiency<sup>2</sup></b>	<b>η</b> [%]	≥ 16.2	≥ 16.4	≥ 16.7	≥ 16.9	≥ 17.2
<b>MINIMUM PERFORMANCE AT NORMAL OPERATING CONDITIONS, NOC<sup>3</sup></b>							
Minimum	<b>Power at MPP<sup>2</sup></b>	<b>P<sub>MPP</sub></b> [W]	232	235	239	243	247
	<b>Short Circuit Current*</b>	<b>I<sub>SC</sub></b> [A]	7.37	7.40	7.44	7.52	7.60
	<b>Open Circuit Voltage*</b>	<b>V<sub>OC</sub></b> [V]	42.9	43.0	43.1	43.2	43.4
	<b>Current at MPP*</b>	<b>I<sub>MPP</sub></b> [A]	6.79	6.88	6.93	7.00	7.09
	<b>Voltage at MPP*</b>	<b>V<sub>MPP</sub></b> [V]	34.1	34.2	34.5	34.7	34.8

<sup>1</sup>1000W/m<sup>2</sup>, 25°C, spectrum AM 1.5G    <sup>2</sup>Measurement tolerances STC ±3%; NOC ±5%    <sup>3</sup>800W/m<sup>2</sup>, NOCT, spectrum AM 1.5G    \*typical values, actual values may differ


## Q CELLS PERFORMANCE WARRANTY



At least 97% of nominal power during first year. Thereafter max. 0.6% degradation per year.  
At least 91.6% of nominal power up to 10 years.  
At least 83.0% of nominal power up to 25 years.

All data within measurement tolerances. full warranties in accordance with the warranty terms of the Q CELLS sales organization of your respective country.

## PERFORMANCE AT LOW IRRADIANCE



Typical module performance under low irradiance conditions in comparison to STC conditions (25°C, 1000W/m<sup>2</sup>).

## TEMPERATURE COEFFICIENTS

<b>Temperature Coefficient of I<sub>SC</sub></b>	<b>α</b> [%/K]	+0.05	<b>Temperature Coefficient of V<sub>OC</sub></b>	<b>β</b> [%/K]	-0.31
<b>Temperature Coefficient of P<sub>MPP</sub></b>	<b>γ</b> [%/K]	-0.40	<b>Normal Operating Cell Temperature</b>	<b>NOCT</b> [°C]	45 ± 3

## PROPERTIES FOR SYSTEM DESIGN

<b>Maximum System Voltage</b>	<b>V<sub>sys</sub></b> [V]	1000 (IEC), 1500 (IEC)	<b>Safety Class</b>	II
<b>Maximum Reverse Current</b>	<b>I<sub>r</sub></b> [A]	20	<b>Fire Rating</b>	C
<b>Push/Pull Load (Test-load in accordance with IEC 61215)</b>	[Pa]	5400/2400	<b>Permitted Module Temperature On Continuous Duty</b>	-40°C up to +85°C

## QUALIFICATIONS AND CERTIFICATES

IEC 61215, IEC 61730, Conformity to CE, Application Class A



## PARTNER

**NOTE:** Installation instructions must be followed. See the installation and operating manual or contact our technical service department for further information on approved installation and use of this product.

Hanwha Q CELLS (Qidong) Co., Ltd.  
No. 888 Linyang Road, Qidong City, Jiangsu Province, China | EMAIL sales@hanwha-qcells.com | WEB www.q-cells.com

Engineered in Germany

**Q CELLS**